

Model IPS-4 Integrated Process Spectrophotometer

THE NEED

Today's chemical producers and consumers are under tremendous pressure to cut costs, lower maintenance expenses, and improve product quality. In order to meet these demanding objectives, process engineers and operators need analytically capable and reliable process analyzers which require minimal maintenance and operator intervention. The analyzers also need to be easy to use and capable of communicating in a wide variety of ways. It is also a benefit if the analyzer is durable enough to be installed in outdoor, wash-down, hazardous, and other environmentally harsh locations.

THE SOLUTION

AMETEK's Western Research® IPS-4 is a huge step forward in capability and reliability for process spectrophotometers. Using the most modern electronics and diode array technology, the IPS-4 is engineered to perform a wide variety of liquid and gas analyses using UV-VIS spectroscopy.

Analytical Performance

The IPS-4 is capable of detecting, quantifying, and compensating for multiple chemicals of interest and interfering species. Up to eight components of interest can be measured simultaneously through the combination of a modern, diode array-based optical system with our proprietary process-ready electronics.

This combination offers many advantages such as no moving parts, a high signal-to-noise ratio, minimized stray light effects, fast and full spectral acquisition, and wide dynamic range. These traits help to make the IPS-4 a highly capable process analyzer.

Optical System

The IPS-4's optical system is designed to increase reliability and dramatically reduce the need for routine maintenance, thereby drastically cutting its cost of ownership. The lamp



Western Research Model IPS-4


used in the optical system is a xenon flash lamp which has an amazing >2 year expected life. Use of the diode array and fixed optical bench means that there is no filter wheel or motor to maintain, no optical filters to replace, and no optical couplings to align. The resulting optical system is small, insensitive to mechanical tolerances, insensitive to movement, and free of moving parts.

The AMETEK designed electronics are engineered to withstand harsh outdoor, industrial environments. They possess excellent temperature stability, reliability, and a host of self-diagnostic and predictive maintenance capabilities. The combined result of the IPS-4's design is a spectrophotometer with high reliability and a minimal need for routine maintenance.

Interface Options

Manufacturing facilities have a wide variety of communication needs from their process analyzers. To meet the varied needs of our customers, we have equipped the IPS-4 with numerous analog and digital communications capabilities. A detailed, multi-line display along with a 22-key keypad provides the primary local indications. The keypad is a stainless steel, piezo-electric device which is the ultimate in durability and reliability. The pixel-based display is detailed enough to allow for a selection of display language. The analyzer also communicates through a variety of analog signals, alarm contacts, and three types of digital communication.

Digital communication options include a RS232, RS485 with MODBUS RTU protocol, and a built-in Fast Ethernet port.



Wide Environmental Tolerance

Process analyzers must often be installed in harsh environments. Unlike other process analyzers, the IPS-4 is designed to handle most environmental challenges without the need for additional protection or prohibitively expensive shelters.

The IPS-4 is supplied in an IP65 enclosure which exceeds the requirements of NEMA4. This enclosure is more than capable of handling even wash-down environments without allowing water or dust to ingress. The standard enclosure is a painted steel chassis although a stainless steel chassis is available.

When installed outdoors, the IPS-4 will tolerate ambient temperatures from -20° to 50° C (-4° to 122° F) without external heating/cooling. When installed indoors, the analyzer takes up minimal space as it is designed with a very narrow profile. The width of the IPS-4 has been kept to only 78 cm (<31 inches) to minimize the amount of precious wall space it occupies. This narrow width is maintained even when a wide range of custom sample handling and conditioning systems are integrated into the IPS-4's sample cell enclosure.

Custom Sampling Systems

The IPS-4 is engineered to be a fully integrated, turn-key solution to your specific process analysis need. AMETEK will engineer a sample handling and conditioning system to meet the requirements of your sample fluid and application. Automatic zero and span fluid injection, corrosion-resistant materials, filtration, pumps or eductors, and heated sample lines are a few of the customizations AMETEK will engineer into the IPS-4 to meet your specific requirements.

The IPS-4 may be the solution you need to improve the quality and efficiency of your process. Contact your AMETEK Process Instruments salesperson to discuss your specific application today.

DIMENSIONS (or Charts)

FEATURES AND BENEFITS

- Measures up to eight wavelengths
- Low cost of ownership
- Lamp life greater than two years
- No moving parts
- IP65, weatherproof
- Integrated, customizable sample system
- Fast Ethernet and MODBUS communications

PERFORMANCE SPECIFICATIONS

Photometric Range: 0 to 3.0 AU; Minimum Full Scale is 0.1 AU at specified precision

Analyzer Range: ppm to 100% depending upon specific application

Measurement Precision: <1% of full scale range

Zero drift: <1 % of full scale range over 24 hours

Linearity: Less than 1% of full scale range

Response Time: <2 seconds for the photometric measurement. Total system response depends upon sample system.

Components

Inputs:

- 2 non-isolated analog inputs (0-5V, 0/4-20mA)
- 2 optically isolated discrete DC inputs
- 22 key piezoelectric keypad

Outputs:

- 265x64 pixel vacuum fluorescent display with multi-lingual capability
(Language options include: English, Spanish, French, German, Russian. This is a partial listing. Contact AMETEK for more information.)
- 2 isolated analog outputs (0/4-20 mA)
(Two additional analog outputs optional)
- 8 dry relay contacts (NO, 100VA, 300Vmax)
- RS485 isolated (supports MODBUS RTU)
- RS232 non-isolated
- Fast Ethernet (IEE802.3)

Sample System Limits

Sample Pressure: Up to 100 barg (1450 psig) for some configurations

Oven Temperature: Oven heater capable of maintaining 150° C (300° F)

Number of measured: Up to eight components can be measured

Utility Requirements

Electrical:

- 120 VAC (105 to 132 VAC), 47 to 63 Hz
- 240 VAC (209 to 264 VAC), 47 to 63 Hz

Power consumption:

- < 700 W with oven heater
- < 300 W without oven heater

Instrument Air: 4.8 – 6.9 barg (70 - 100 psig)

Environmental Requirements

Ambient Temperature: -20° C to 50° C (-4° to 122° F) without external heating or cooling

Ingress Protection: IP65 (better than NEMA 4)

Enclosure material: Painted steel, stainless steel optional

Physical dimensions:

(W x H x D): 78 cm x 53 cm x 30 cm (30.7" x 20.9" x 11.8")

Weight: 66 kg (145 lb) for base system

Approvals and Certifications (pending)

NEC/CEC General Safety requirements

CE

NEC/CEC Class I, Division 2, Groups ABCD

NEC/CEC Class I, Division 1, Groups ABCD

ATEX and IEC Ex II 2 (and 3) G IIC T3

One of a family of innovative process analyzer solutions from AMETEK Process Instruments. Specifications subject to change without notice.

USA - Pennsylvania
150 Freeport Road
Pittsburgh, PA 15238
Ph. 412-828-9040
Fax 412-826-0399

MANUFACTURING
LOCATIONS



CANADA
2876 Sunridge Way N.E.
Calgary, AB T1Y 7H9
Ph. 403-235-8400
Fax 403-248-3550

USA - Delaware
455 Corporate Blvd.
Newark, DE 19702
Ph. 302-456-4400
Fax 302-456-4444

AMETEK®
PROCESS INSTRUMENTS
www.ametekpi.com

© 2005, by AMETEK, Inc. All rights reserved.
IPS-F (06/02/05)

USA - Oklahoma
2001 N. Indianwood Ave.
Broken Arrow, OK 74012
Ph. 918-250-7200
Fax 918-459-0165

**SUPPORT
LOCATIONS**

USA - Texas
Ph. 281-463-2820
Fax 281-463-2701

CHINA - Beijing
Ph. 86-10-85262111
Fax 86-10-85262141

CHINA - Shanghai
Ph. 86 21 6426 8111
Fax 86 21 6426 7054

FRANCE
Ph. 33 1 30 68 89 00
Fax 33 1 30 68 89 99

GERMANY
Ph. 49 21 59 91 36 0
Fax 49 21 59 91 3680

MIDDLE EAST - Dubai
Ph. 971-4-881 2052
Fax 971-4-881 2053

SINGAPORE
Ph. 65-6484-2388
Fax 65-6481-6588