

# PRODUCT DATA SHEET

## CEM/Oxygen Analyzer

Extractive net oxygen (O<sub>2</sub>) analyzer for use in a wet or dry gas continuous emission monitoring (CEM) system or instrument cabinet

For applications where a sample is taken to a remote analyzer location, the cost-effective CEM/O<sub>2</sub> analyzer provides advanced system features that integrate into your overall emissions monitoring system.

The analyzer complies with 40 CFR Part 60 and Part 75 Federal EPA performance specification requirements along with regional requirements for O<sub>2</sub> monitors.

### Extractive analyzers

Extractive analyzers are located remotely from the sample point. The sample can be delivered to the analyzer through a heated sample line (hot or wet) or cooled to remove the moisture (dry). With zirconium oxide (ZrO<sub>2</sub>), either method can be used. Most of the sample passes straight through the analyzer. A portion flows into the convection loop and is measured by the O<sub>2</sub> cell.

### Series 2000 control unit

Series 2000 microprocessor control provides four-line local display, analog outputs, alarms, expanded system diagnostics, autocalibration option, RS485 communication, and optional Humox O<sub>2</sub> wet/dry calculation software for correlated flue gas moisture measurement.



## KEY BENEFITS

- Wet or dry gas
- Small footprint
- Easy to operate

## APPLICATIONS

- CEM system
- Wet or dry O<sub>2</sub> measurement

## KEY MARKETS

- Industrial

## PERFORMANCE SPECIFICATIONS

## Sensor Specifications

<b>Principle of operation</b>	ZrO <sub>2</sub>
<b>Operating range</b>	0.1-100% O <sub>2</sub>
<b>Accuracy</b>	±0.75% of reading or 0.05% O <sub>2</sub> , whichever is greater
<b>Response time</b>	Less than 4 seconds at 2 scfh from 2% O <sub>2</sub> to 20% O <sub>2</sub>
<b>Drift</b>	<0.1% of cell output per month, (<0.005% O <sub>2</sub> per month with 2% O <sub>2</sub> applied)
<b>Max. inlet temperature</b>	204°C (400°F)
<b>Sample pressure</b>	±2 psig max (0.14 kg/cm <sup>2</sup> )
<b>Sample flow</b>	2 to 20 scfh (0.94 to 9.4 L/min)
<b>Environment</b>	Ambient temperature: -18 to 50°C (0 to 122°F). Relative humidity: 10-90%, non-condensing
<b>Enclosure</b>	Indoor use only
<b>Power requirements</b>	115 VAC, ±10%, 47-63 Hz; 230 VAC, ±10%, 47-63 Hz, 1670 VA max.
<b>Calibration gas requirement</b>	Use calibration gases at 2-20 scfh (0.94-9.4 L/min) Zero gas: From 0.1-10% O <sub>2</sub> , balance nitrogen Span gas: Minimum one decade above zero gas (10 times greater)

## Series 2000 Control Unit

<b>Display</b>	Four-line x 20-character vacuum fluorescent. Displays combinations of time and date, cell temperature, user-programmable text, thermocouple mV or cell mV. Password protection, programmable pressure compensation and context sensitive help are also provided
<b>Analog output</b>	Two isolated linear current outputs. Select O <sub>2</sub> , cell temperature, thermocouple mV or cell mV. Each output can be 4-20 mA, 0-20 mA, 20-4 mA or 20-0 mA, and is fully scalable. Hold or track during calibration and select degree of damping. Maximum load 1200 ohms
<b>Alarms</b>	Two independent O <sub>2</sub> alarms, each high or low selectable. One alarm can be assigned as O <sub>2</sub> , calibrate or verify. Set relays to energize or de-energize on alarm
<b>Contact rating</b>	0.5A, 30V, 10VA max. non-inductive load, AC or DC
<b>Diagnostics</b>	Watchdog timer and service alarms. System test for A/D, RAM, EEPROM and keypad. Display line four reserved for full text error and diagnostic messages. 20-entry exception log for automatically detected system events
<b>Communications</b>	RS-485, two-way addressable
<b>Environment</b>	Ambient temperature: -10 to 50°C (14 to 122°F). Relative humidity: 10-80%, non-condensing
<b>Enclosure</b>	Standard general purpose (GP) 19" rack mount. Optional GP panel or wall mount, weatherproof NEMA 4 (IP56) and NEMA 4X (IP56) enclosures available. All are UL Listed for NEC Class I, Division 2 areas
<b>Calibration</b>	Store last calibration and verification data. Selectable calibration gas run time and process recovery time Timed automatic calibration with optional Remote Calibration Unit. O <sub>2</sub> cell lifetime extender Single gas verification that analyzer is within calibration limits
<b>Power requirements</b>	Nominal 115-230 VAC ±10%, 47-63 Hz, 75 VA max.
<b>System compliance</b>	EMC directive 89/336/EEC. Low voltage directive 73/23/EEC

## SALES, SERVICE &amp; MANUFACTURING

## USA - Pennsylvania

150 Freeport Road  
Pittsburgh PA 15238  
Tel: +1 412 828 9040  
Fax: +1 412 826 0399

## USA - Delaware

455 Corporate Blvd.  
Newark DE 19702  
Tel: +1 302 456 4400  
Fax: +1 302 456 4444

## Canada - Alberta

2876 Sunridge Way NE  
Calgary AB T1Y 7H9  
Tel: +1 403 235 8400  
Fax: +1 403 248 3550

## WORLDWIDE SALES AND SERVICE LOCATIONS

## USA

Tel: +1 713 466 4900  
Fax: +1 713 849 1924

## Brazil

Tel: +55 19 2107 4100

## France

Tel: +33 1 30 68 89 20  
Fax: +33 1 30 68 89 99

## Germany

Tel: +49 2159 9136 0  
Fax: +49 2159 9136 39

## India

Tel: +91 80 6782 3200  
Fax: +91 80 6780 3232

## Singapore

Tel: +65 6484 2388  
Fax: +65 6481 6588

## China

Beijing  
Tel: +86 10 8526 2111  
Fax: +86 10 8526 2141  
Chengdu  
Tel: +86 28 8675 8111  
Fax: +86 28-8675 8141  
Shanghai  
Tel: +86 21 5868 5111  
Fax: +86 21 5866 0969



© 2018, by AMETEK, Inc. All rights reserved. Printed in the U.S.A. F-0381 Rev 5 (0818)  
One of a family of innovative process analyzer solutions from AMETEK Process Instruments. Specifications subject to change without notice.



To find out more or request a quote visit our website

[ametekpi.com](http://ametekpi.com)