

PRODUCT DATA SHEET

PreMix 2000 Air/Fuel Ratio Analyzer for Premix Burners

Permanent installation sensor for control of fiberizing lines and other pre-combustion applications

The PreMix 2000 analyzer accurately and continuously measures the proportions of oxygen (O₂), and fuel in pre-mix gases, operating in either excess fuel or excess air conditions. The analyzer is fed a small sample of the air/fuel mixture, burns it and then measures the net O₂ or net excess fuel content of the mixture.

Operation

Most of the sample gas entering the analyzer passes through the bypass flow meter, which ensures a fast response and keeps the sample inlet purged of dead volume. A small portion of the sample flows through the sample flow meter and flashback arrestor to the furnace. An igniter at the inlet of the furnace enables the fuel mixture to burn. The products of combustion then flow past the zirconium oxide cell, where they are measured.

Control unit

The PreMix 2000 uses the Series 2000 control unit. This state-of-the-art microprocessor control unit provides software-selectable calibration options, and extensive analog and digital I/O capabilities, including a bi-directional RS-485 communications port. It also employs a modular design that makes adding future upgrades or servicing easy.



KEY BENEFITS

- Measure air/fuel ration in open-flame application where flue gas measures are not practical
- Measurement and display options include excess O₂, excess fuel, air/fuel ratio and combustibles
- Operates under either excess air (lean) or excess fuel (rich) conditions
- Calculates calibration gas mixture concentration for excess fuel ranges

APPLICATIONS

- Glass forehearth
- Air/fuel mixtures
- Glass fiber apparatus
- Open flame brazing and soldering
- Temperature furnaces
- Gas generators
- Metals and metal forming

KEY MARKETS

- Glass fiber manufacturer
- Glass melting tanks

PERFORMANCE SPECIFICATIONS

Sensor Specifications

Range	All or selected portions of the range from 100% to 0.1% excess O ₂ and 0.1% to 50% excess fuel
Accuracy	± 2% of measured value or ± 0.1% O ₂ , whichever is greater; ± 5% of measured value or 0.25% excess fuel, whichever is greater
Repeatability	± 0.2% of measured value
Ambient temperature	-5 to 158°F (-20 to 70°C)
Sample flow rate	0.5 L/min. (1 scfh)
Bypass flow rate	- 50 L/min. max. (106 scfh)
Max sample pressure	10 psig
Power	115 VAC ± 10%, 50/60 Hz., 1200 VA max.; 230 VAC ± 10%, 50/60 Hz., 2400 VA max
Excess oxygen calibration gases	O ₂ span gas: 20.9% (air) or from 1.0 to 100% O ₂ , balance nitrogen (N ₂); O ₂ zero gas: 2% or from 0.1% to 10% O ₂ , balance N ₂
Excess fuel calibration gases	Methane (CH ₄)/O ₂ /N ₂ Span: 40 to 60% of recorder output span; CH ₄ /O ₂ /N ₂ Zero: 5 to 10% of recorder output span
Enclosure	UL Type 3R (IP14)

Control Unit Specifications

Display	Four-line x 20-character vacuum fluorescent; Displays combinations of excess O ₂ , excess fuel, combined O ₂ to excess fuel range, air/fuel ratio, combustibles, time and date, cell temperature, user programmable text, thermocouple mV, or cell mV; Password protection and context sensitive help are provided
Analog output	Two isolated linear current outputs. Select excess O ₂ , excess fuel, combined excess O ₂ to excess fuel range, combustibles, air/fuel ratio, cell temperature, thermocouple mV or cell mV. Each output can be 4-20 mA, 0-20 mA, 20-4 mA or 20-0 mA and is fully scalable. Hold or track during calibration and select degree of damping; Maximum load 1200 ohms
Alarms	Two independent alarms, each high or low selectable. One alarm can be allocated to sensor readings, calibrate or verify Set relays to energize or de-energize on alarm
Contact rating	0.5A, 30V, 10VA max. noninductive load, AC or DC
Diagnostics	Watchdog timer and service alarms. System test for A/D, RAM, EEPROM, and keypad. Display line four reserved for full text error and diagnostic messages. 20 entry event log
Communications	RS-485, 2-way addressable
Ambient temperature	14°F to 122°F (-10°C to 50°C)
Relative humidity	10% to 90%, non-condensing
Enclosure	Standard weatherproof NEMA 4 (IP 56) wall/panel mount. Optional GP (General Purpose) wall mount, GP 19" rack mount, GP panel mount, or stainless steel weatherproof NEMA 4X (IP 56) wall/panel mount. All are UL Listed for NEC Class I, Division 2 areas. Purged and explosion-proof versions also available
Power requirements	Nominal 115-230 VAC ± 10%, 47-63 Hz, 75 VA max
System compliance	EMC Directive 2004/108/EC; Low Voltage Directive 73/23/EEC

SALES, SERVICE & MANUFACTURING

USA - Pennsylvania

150 Freeport Road
Pittsburgh PA 15238
Tel: +1 412 828 9040
Fax: +1 412 826 0399

USA - Delaware

455 Corporate Blvd.
Newark DE 19702
Tel: +1 302 456 4400
Fax: +1 302 456 4444

Canada - Alberta

2876 Sunridge Way NE
Calgary AB T1Y 7H9
Tel: +1 403 235 8400
Fax: +1 403 248 3550

WORLDWIDE SALES AND SERVICE LOCATIONS

USA

Tel: +1 713 466 4900
Fax: +1 713 849 1924

Brazil

Tel: +55 19 2107 4100

France

Tel: +33 1 30 68 89 20
Fax: +33 1 30 68 89 99

Germany

Tel: +49 2159 9136 0
Fax: +49 2159 9136 39

India

Tel: +91 80 6782 3200
Fax: +91 80 6780 3232

Singapore

Tel: +65 6484 2388
Fax: +65 6481 6588

China

Beijing
Tel: +86 10 8526 2111
Fax: +86 10 8526 2141
Chengdu
Tel: +86 28 8675 8111
Fax: +86 28-8675 8141
Shanghai
Tel: +86 21 5868 5111
Fax: +86 21 5866 0969



© 2018, by AMETEK, Inc. All rights reserved. Printed in the U.S.A. F-0160 Rev 7 (0818)
One of a family of innovative process analyzer solutions from AMETEK Process Instruments. Specifications subject to change without notice.



To find out more or request a quote visit our website

